

## A1025/AR1000

### AROX Griddle

Electric/Gas - Free-standing



#### Features

Our griddle is available in two operating modes: electric (A1025) or gas (AR1000).

The fry top is distinguished by a thick and highly polished steel griddle plate, smooth or covered by shiny chrome with high conductivity.

All griddles are equipped with a splash guard welded on the working plate for hygiene. Our equipment are also supplied with a waste collecting grease channel to collect grease and oil in a lift-off drawer with a capacity of 2.5ltrs.

A1025 is fitted with armoured stainless steel elements ordered by an electric thermostat and safety hand resetting thermostat.

AR1000 is supplied by a thermostatic gas valve with a complete safety system connected to a thermocouple and pilot flame.

#### Specifications

|                      |  |
|----------------------|--|
| Width (mm)           | 400  |
| Depth (mm)           | 700  |
| Height (mm)          | 850  |
| Net / Gross Wt (kg)  | 55 / 60                                      |
| Rating (kw)          | 4.5 (A1025) / 5.5 (AR1000)                   |
| Voltage (A1025 only) | 380-415V / 3ø / 50Hz<br>440-480V / 3ø / 60Hz |

Continuing research results in steady improvements; therefore, these specifications are subject to change without prior notice.

Images for reference only; actual products may vary.