

# ALS-680

## AROX Tumble Dryer

Commercial range  
Electric



### Features

- Stainless Steel Drum AISI 430 with 1mm thickness.
- Huge Door Opening (Diameter 810mm) for easy loading & unloading.
- Large & strong resistant synthetical filter for easy cleaning.
- Efficient operation and very short drying times.
- Ideal ventilation.
- Axial airflow.
- Rubber seal: EPDM quality resistant to extreme conditions.
- Door can be mounted left or right with opening to 180°.
- Safety Emergency button on front.
- Easy Control with minimum cool down.

### Specifications

Dimensions	Millimeters (mm)	
Width	965	
Depth	1490	
Height	1975	
<b>Capacity</b>	<i>Ratio: 1/20</i>	35 kg (77 lbs)
<b>Drum Vol</b>	680 litres	
<b>Door Size</b>	Dia 810 x d1000 mm	
<b>Airflow</b>	1500 m <sup>3</sup> /h	
<b>Drying Average</b>	0.560 l/min	
<b>Rating</b>	36 kW	
<b>Voltage</b>	440 V / 3ø / 60Hz	
<b>Air Outlet</b>	Dia 200 mm	
<b>Net / Gross Weight</b>	305 / 330 Kg	

#### Min space of positioning:

- Rear of Dryer to wall ~ 600mm
- Between Dryers / side wall ~ 20mm
- Top of Dryer to Ceiling ~ 500mm

Continuing research results in steady improvements; therefore, these specifications are subject to change without prior notice.  
Images for reference only; actual products may vary.